



Chroma-Q®
BRILLIANT SOLUTIONS

Specification Sheet - Version: 1.0 US
Chroma-Q® 2inspire™ 100/200/300 POE
Part No: CQ150X-10YY



DESCRIPTION

The new Chroma-Q® 2inspire™ family delivers truly flexible lighting into any space quickly and efficiently.

2inspire™ is a compact, silent, bright fixture, available in 3 sizes. These installation luminaires deliver studio-grade tuneable white light and pure theatrical quality colors.

A holistically designed accessory collection easily mounts each fixture - on a wall, as a pendant, in a ceiling or from a yoke.

Innovative technology minimises deployment costs and maximises efficiency, making every 2inspire™ flexible, sustainable and durable.

FEATURES

- RGB-CW-WW colour system for an extended color rendering
- Ethernet POE connection
- 500, 1200, 3000 lumens
- Multiple mounting accessories

ORDERING INFORMATION

CQ150X-1000: 2inspire POE RGBWWCW IP20 black body

CQ150X-1005: 2inspire POE RGBWWCW IP20 white body

CQ150X-1010: 2inspire POE RGBWWCW IP65 black body

CQ150X-1015: 2inspire POE RGBWWCW IP65 white body

** replace X by 1=100, 2=200, 3=300

ACCESSORIES

CQ1509-9005 Wall mount short black

CQ1509-9006 Wall mount short white

CQ1509-9017 Pendant mount kit (w/o stem, w/o yoke) black **

CQ1509-9018 Pendant mount kit (w/o stem, w/o yoke) white **

CQ1509-9021 Pendant stem 1ft, 300mm black

CQ1509-9022 Pendant stem 1ft, 300mm white

CQ1509-9025 Pendant stem 2ft, 600mm black

CQ1509-9026 Pendant stem 2ft, 600mm white

CQ1509-9029 Pendant stem 3ft, 900mm black

CQ1509-9030 Pendant stem 3ft, 900mm white

CQ1509-9X13 Yoke black**

CQ1509-9X14 Yoke white**

CQ1509-9X33 Shroud for pendant mount kit black**

CQ1509-9X34 Shroud for pendant mount kit white**



Accessories (cont'd)

CQ1509-9X37 Blind ceiling mount 0° black**

CQ1509-9X38 Blind ceiling mount 0° white**

CQ1509-9X41 Blind slant ceiling mount 0-45° black**

CQ1509-9X42 Blind slant ceiling mount 0-45° white**

CQ1509-9X60 Honeycomb louver black**

CQ1509-9X61 Honeycomb louver white**

CQ1509-9X62 Barndoor black**

CQ1509-9X63 Barndoor white**

CQ1509-9X64 Snoot black**

CQ1509-9X65 Snoot white**

CQ1509-9X66 Medium diffusion (pack of 10)**

CQ1509-9X67 Wide diffusion (pack of 10)**

CQ1509-9X68 Extra wide diffusion (pack of 10)**

CQ1509-9X69 Assymetrical diffusion (pack of 10)**



Chroma-Q®
BRILLIANT SOLUTIONS

Specification Sheet - Version: 1.0 US
Chroma-Q® 2inspire™ 100/200/300 POE
Part No: CQ150X-10YY

OVERALL SPECIFICATIONS

2inspire™ 100

Net Dimensions W: 93mm x H: 93mm x D: 108mm
(without fixings): W: 3.7" x H: 3.7" x D: 4.3"
Net Weight: 0.62kg / 1.4lb

2inspire™ 200

Net Dimensions W: 118mm x H: 118mm x D: 145mm
(without fixings): W: 4.7" x H: 4.7" x D: 5.7"
Net Weight: 1.15kg / 2.5lb

2inspire™ 300

Net Dimensions W: 147mm x H: 147mm x D: 195mm
(without fixings): W: 5.8" x H: 5.8" x D: 7.7"
Net Weight: 2.5kg / 5.1lb

Color mixing: RGB WW CW
Color Temp Control: Variable 2400 - 6500K
Tint Control: -2 to +2
Control Protocol: Artnet / sACN / RDM
RDM compliance: Yes
LED Pixels: 1
Control Modes: I single channel intensity
IK intensity and CCT
IKT intensity, CCT, tint
RGB RGB+magic white
IRGB intensity and RGB+magic white
IHS intensity, hue and saturation
IKTRGB intensity, CCT, tint, RGB+magic white
IKTHS intensity, CCT, tint, hue, saturation;
RGB-WW-CW RGB warm-white and cold-white

DMX Channels: 1 to 13
Dimming Curve: Linear, Inverse square-law, square-law, S-curve
Setting and Addressing: Through Art-Net RDM
Hot Lumen Output: 500 / 1200 / 3000 lumens (preliminary)
Optics: Fully homogenised
Beam Angle: 22° / 22° / 30° (approx)
Optional Diffusion: 36, 65, 80, Assymetrical
Beam Distribution: Symmetrical
Colour Engine: ColorSure™ calibrated engine
CCT: 2400-6500K
Colour Gamut Ratio: sRGB=151%; NTSC=107%; AdobeRGB=112%;
DCI-P3=112%;REC.2020=80%

CRI: >90
TLCI: >90

IES TM-30-18 Rf >90
IES TM-30-18 Rg <100 to 103
Lamp Life: <L70 50,000hr
Power & Data
Connector In: RJ45 Ethernet POE
Mounting points: Multi
Orientation: Any
Construction: Anodised black aluminum cast
Powder coated white aluminum cast

Colour: Black RAL 9005/ White RAL 9016
IP Rating: IP20 / Optional IP65
Power Supply: 802.3at / 802.3bt Class A / Class B
Power Input Rating: 50-57 VDC
Power Consumption: 25W / 50W / 75W
Idle Power Consumption: 3W
Cooling System: Natural Convection
Max Surface Temperature: Ta=60°C
Operating Temperature: -20°C to 40°C
Total heat dissipation: 85 / 171 / 256 BTU/hr
Approvals: CISPR 22 :2006/EN55022 :2006 & CISPR 24
:1997/EN55024 :1998; ICES-003 :2004 & FCC Part
15 Subpart B: 2007; CSA C22. No.
166-M1983:R2008; UL 1573:2003; UL 8750



www.chroma-q.com

Chroma-Q and all associated product names are recognised trademarks, for more information visit www.chroma-q.com/trademarks. The rights and ownership of all trademarks are recognised. Whilst every effort has been made to ensure that the information is correct, Chroma-Q accepts no liability for errors or omissions. Technical specifications and data are provided for guidance only. Because we constantly aim to improve our products, we reserve the right to amend or alter at any time and without prior notice, the specifications of any product. E&OE.