

IES Photometric Report 2inspire 200

Chroma-Q_2inspire_200_Extra_Wide_4800K_PendantMount_P2.IES



Generated: 5/4/2026 2:10:08 PM

Generated: 5/4/2026 2:10:08 PM

Fixture Information


Manufacturer	Chroma-Q	Max Candela	892.7 cd
Luminaire	LED Projector Luminaire at 4800K setting	Est. Total Lumens	959 lm
Lamp	LEDs	Beam Angle (50%)	45.9°
Format	IESNA:LM-63-2002	Field Angle (10%)	126.4°
Wattage	34.0 W	Phot. Type	Type C (Vertical)
Lumens/Lamp	959 lm	Units	Meters
Num Lamps	1	W x L x H	-0.120 x -0.120 x 0.000
Ballast Factor	1.000		


Photometric Data


V Angles	181 (0° – 180°)
H Angles	25 (0° – 360°)

IES Keywords

[TEST]	EV-2002
[TESTLAB]	Spectrum mfg
[TESTDATE]	02-07-2025
[MANUFAC]	Chroma-Q
[LUMCAT]	2inspire-POE-200_Extra_Wide_PendantMount(4800K)
[LUMINAIRE]	LED Projector Luminaire at 4800K setting
[LAMP]	LEDs
[BALLAST]	DC
[BALLASTCAT]	
[_VOLTAGE]	68.08
[_CURRENT]	0.5
[_WATTAGE]	34.04
[_PF]	0.56
[_THD]	0.0
[_LUMENS]	959.08
[_EFFICACY]	28.17
[_STABILIZATION TIME]	70








Settings


Distance unit **Meters (m)**
Light unit **Lux (lx)**
Spread mode **Fixture count**
C-Plane **All C-Planes**
Output Height **1.6 m**
Floor X **5.0 m**
Floor Y **5.0 m**
Fixture grid **1 x 1 (1)**
Wall dist X **0.30 m**
Wall dist Y **0.30 m**

Results


Peak **133.1 lx**
Average **24.2 lx**
Min **1.7 lx**
Result grid **6 x 6 @ 1.0 m**



Iso-Illuminance



Beam Intensity



* at beam centre