



Chroma-Q™
BRILLIANT SOLUTIONS

Specification Sheet - Version: 1.3

Chroma-Q™ 4Play™

4 Way DMX Buffer

Part No: CHDMX4

DESCRIPTION

The device shall be a fault tolerant, self healing 4 way DMX buffer designed to fully isolate all outputs from the input and each other.

FEATURES

- 4 way DMX buffer.
- Fault tolerant, self healing.
- Each output fully isolated.
- 4 x 5 pin XLR connector outputs.
- 1 x 5 pin XLR connector input and through.
- Each output is separately generated and boosted from the original DMX signal.
- Data and power indicators.
- Suitable for truss mounting with a normal hook clamp.
- Will work with mains voltages worldwide (100-240V, 50/60Hz).
- Supplied with a chassis mounted IEC male to assist international cabling

OVERALL SPECIFICATIONS

Net dimensions: Width (A): 148mm / 5.9"
 Height (B): 158mm / 6.3"
 Depth (C): 40mm / 1.6"

Net weight: 0.6kg / 1.3lbs

Colour: Black


Power: 100-240V, 50-60Hz, 15W

Power connector: IEC chassis male

DMX connector In: XLR5

DMX connector Out: 4 x XLR5

DMX connector Thru: XLR5



ORDERING INFORMATION

CHDMX4: Chroma-Q 4Play 4 Way DMX Buffer.